

## Hydraulic separator CPN 100 - DN 40 (1 1/2")

### Equipment:



**TBN 100**  
(optional)



Hydraulic separator **CPN 100 DN 40** is made of steel. The factory is equipped with insulation, and the upper side with two connections for the temperature sensor and a vent (coupler 1/2" M), and the lower side of the drain connection (coupler 2" F). In the set they are automatic air vent 3/8" with check valve 1/2", immersion sleeve for temperature sensor 1/2", four cast-iron fittings 1 1/2" and mounting feet.

### Technical data:

Raw material:	steel ST 37.1
Max pressure:	8 bar
Flow rate:	6,5 m <sup>3</sup> /h
Max temp.:	110°C
Insulation material:	EPP black 40 g/l
Connections:	1 1/2"

Type	Catalog number
Hydraulic separator <b>CPN 100 - DN 40</b> with equipment	607002
Insulated tubing kit <b>TBN 100/2 - DN 32</b> for connection <b>C 100 2F - DN 25</b> with <b>CPN 100 - DN 40</b>	607005
Insulated tubing kit <b>TBN 100/3 - DN 32</b> for connection <b>C 100 3F - DN 25</b> with <b>CPN 100 - DN 40</b>	607006
Insulated tubing kit <b>TBN 100/4 - DN 32</b> for connection <b>C 100 4F - DN 25</b> with <b>CPN 100 - DN 40</b>	607007
Insulated tubing kit <b>TBN 100/5 - DN 32</b> for connection <b>C 100 5F - DN 25</b> with <b>CPN 100 - DN 40</b>	607008
Insulated tubing kit <b>TBN 100/6 - DN 32</b> for connection <b>C 100 6F - DN 25</b> with <b>CPN 100 - DN 40</b>	607009

