

## Hydraulic separator **CPN 60 - DN 20 (3/4")**

### Equipment:



35 kW

**TBN 60**  
(optional)



Hydraulic separator **CPN 60 - DN 20** is made of steel. The factory is equipped with insulation, the upper side with two connections for the temperature sensor and a vent (coupler 1/2" F), and the lower side of the drain connection (coupler 1/2" F). In the set they are automatic air vent 3/8" with check valve 1/2", immersion sleeve for temperature sensor 1/2" and drain valve 1/2".

### Technical data:

Material:	steel ST 37.1
Max pressure:	8 bar
Max flow:	1,7 m <sup>3</sup> /h
Max temperature:	110°C
Insulation material:	EPP czarna 40 g/l
Connections:	
Boiler side:	Nut 1" F
Installation side:	Nut 1" F

Type	Catalog number
Hydraulic separator <b>CPN 60</b> with equipment	605002
Insulated tubing kit <b>TBN 60/2</b> for connection <b>CPN 60 - DN 20</b> with <b>C 60 - DN 20</b>	605005
Insulated tubing kit <b>TBN 60/3</b> for connection <b>CPN 60 - DN 20</b> with <b>C 60 - DN 20</b>	605006
Insulated tubing kit <b>TBN 60/4</b> for connection <b>CPN 60 - DN 20</b> with <b>C 60 - DN 20</b>	605007

