

## Cleanr for central heating installation W-CLEAN 1000



W-CLEAN100 is a professional cleaning agent for central heating systems designed to remove sediment, scale, rust, and other contaminants accumulating inside the system. Regular use improves heat transfer efficiency, extends the life of heating equipment, and prevents breakdowns.

### Technical data:

Capacity:	1L
pH at 20°C:	10.3
Recommended concentration:	1%
Color:	clear

Type	Catalog number
Cleaner for central heating installation W-CLEAN1000	521000

### APPLICATION:

This product is designed for low-temperature, high-temperature, and mixed systems. It works perfectly in systems made of a variety of materials.

### ACTION:

Removes deposits and corrosion from pipes, radiators, and heat exchangers. Improves water flow and reduces heat loss. Can be used with a cleaning pump or directly. Safe for installations – suitable for all system types. Suitable for all water types and materials used in installations.

### USE:

The product is added to the central heating system. Before use, drain enough water to ensure the entire contents of the package reach the circulating system. Then, run the system at full capacity for 2-6 hours until satisfactory performance is restored. After this process, drain and flush the system to remove the product and any contaminants. The system should be topped up with water containing the **W-PROTECT 1000** corrosion inhibitor. This process will significantly improve the circulation of the heating medium and provide long-lasting protection against corrosion and scale. This product is not intended for consumption. Shake thoroughly before use to ensure a uniform product.

### DOSAGE

Use the product at a ratio of 1%, i.e., 1L per 100L of system water. A 1L container is sufficient for a standard domestic installation of up to 10 radiators or 80m<sup>2</sup> of underfloor heating. Higher concentrations are permitted.

### SAFETY ADVICE

**W-CLEAN 1000** cleaning agent, although harmless, requires caution when using it. Keep out of reach of children. If it comes into contact with eyes, rinse with plenty of water. If swallowed, do not induce vomiting. If allergic reactions or skin reactions occur, consult a doctor. Avoid entry into sewers/surface water/groundwater. Dispose of container and contents in accordance with hazardous waste regulations.

### TRANSPORT AND TRANSPORT CONDITIONS

The product should be transported only in its original, closed, and properly secured packaging. The product is not classified as hazardous goods and is therefore not subject to RID/ADR regulations. During transport, the ambient temperature must be maintained at >0°C. Prolonged exposure to sub-zero temperatures should be strictly avoided. The product also requires protection from overheating, direct sunlight, and other influences that may impair its quality parameters.

### STORAGE

The product should be stored only in its original, tightly closed packaging, in closed rooms protected from unauthorized access. Ensure protection from direct sunlight and avoid mechanical damage to the packaging, which could result in uncontrolled leakage. The storage temperature range is 0°C to 35°C. The storage period is the same as the warranty period and is 24 months from the date of production.

### WARRANTY

The cleaning agent is covered by a 24-month manufacturer's warranty. The warranty does not cover packaging damaged mechanically due to improper handling of the product (e.g. throwing, careless transport) or chemically contaminated preparation.

