

Hydraulic separator **CPN 100 - DN 32 (1 1/4")**



Hydraulic separator **CPN 100 DN 32** is made of steel. The factory is equipped with insulation, and the upper side with two connections for the temperature sensor and a vent (coupler 1/2" M), and the lower side of the drain connection (coupler 1/2" M). In the set they are automatic air vent 3/8" with check valve 1/2", immersion sleeve for temperature sensor 1/2", four cast-iron fittings 1 1/4" and wall brackets.

Technical data:

Raw material:	steel ST 37.1
Max pressure:	8 bar
Flow rate:	4,5 m ³ /h
Max temp.	110°C
Insulation material:	EPP black 40 g/l
Connections:	1 1/4"

Type	Catalog number
Hydraulic separator CPN 100 - DN 32 with equipment	607001
Insulated tubing kit TBN 101 / 2 for connection CPN 100 - DN 32 with C 100 2F	617005
Insulated tubing kit TBN 101 / 3 for connection CPN 100 - DN 32 with C 100 3F	617006
Insulated tubing kit TBN 101 / 4 for connection CPN 100 - DN 32 with C 100 4F	617007
Insulated tubing kit TBN 101 / 5 for connection CPN 100 - DN 32 with C 100 5F	617008
Insulated tubing kit TBN 101 / 6 for connection CPN 100 - DN 32 with C 100 6F	617009

