

Hydraulic separator CPN 70 - DN 25

Equipment:



Hydraulic separator **CPN 70** is made of steel. The factory is equipped with insulation, the upper side with two connections for the temperature sensor and a vent (coupler 1/2" F), and the lower side of the drain connection (coupler 1/2" F). In the set they are automatic air vent 3/8" with check valve 1/2", immersion sleeve for temperature sensor 1/2", drain valve 1/2", four cast-iron fittings 1" and wall brackets.

Technical data:

Raw material:	steel ST 37.1
Max pressure:	8 bar
Flow rate:	2,5 m ³ /h
Max temp.:	110°C
Insulation material:	EPP black 40 g/l
Connections:	1"

Hydraulic separator CPN 70 - DN 25 is dedicated to pump group systems. We recommend XPN 25, XPN 32 hydraulic separator for use outside the system.

Type	Catalog number
Hydraulic separator CPN 70 - DN 25 with equipment	606002
Insulated tubing kit TBN 70/2 - DN 25 for connection C 60/70 2F - DN 25 with CPN 70 - DN 25	606005
Insulated tubing kit TBN 70/3 - DN 25 for connection C 60/70 3F - DN 25 with CPN 70 - DN 25	606006
Insulated tubing kit TBN 70/4 - DN 25 for connection C 60/70 4F - DN 25 with CPN 70 - DN 25	606007

